
ENERGY AND AUTOMATION


COMMUNICATION INTERFACE Ø22MM PLATINUM SERIES CHROMED PLASTIC, RJ45 INTERFACE, ETHERNET CONNECTION TYPE



| Product designation | | | RJ45 interface, Ethernet connection type |
|------------------------------------|-----|----|--|
| Product type designation | | | LPCD0 |
| Transmission characteristics | | | Cat.5E |
| General characteristics | | | |
| Material | | | Polyamide |
| IEC degree of protection | | | IP65 on front and IP20 on rear |
| Electrical characteristics | | | |
| Rated insulation voltage Ui IEC/EN | | V | 24VAC |
| Contact resistance | | mΩ | ≤40 |
| Mechanical features | | | |
| Weight | | g | 26 |
| UL technical data | | | |
| UL degree of protection | | | 1, 2, 3R, 4, 4X, 12, 12K on front |
| Ambient conditions | | | |
| Temperature | | | |
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +70 |
| Storage temperature | | | _ |
| | min | °C | -40 |
| | max | °C | +85 |

Dimensions





| | Certifications | and co | mpiiance |
|--|----------------|--------|----------|
|--|----------------|--------|----------|

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508

Certificates

cULus EAC

ETIM classification

ETIM 8.0

EC002780 -Interface module