





Product designation			Single-phase energy meters
Product type designation			DMED100T1
Type			single-phase
DIN rail module number			1
Auxiliary supply Us			
Operational frequency			
-1	min	Hz	50
	max	Hz	60
Power consumption			
	Max	VA	7
Power dissipation Max		W	0.45
Measuring voltage inputs			
Rated voltage (Ue)			
	phase-neutral	VAC	220240
Operating voltage range	P.10000 110001101		
operating vertage range	phase-neutral	VAC	184264
Connection method	prideo rieditai	*****	Direct
Current			Direct
IEC maximum (Imax)		Α	40
IEC minimum (Imin)		A	0.25
IEC rated (Iref-lb)		A	5
IEC start (Ist)		mA	20
Transition (Itr)		A	0.5
Accuracy			0.0
, tooliday			Class 1 (IEC/EN
	Active energy		62053-21)
	Danatina anama		Class 2 (IEC/EN
	Reactive energy		62053-23)
Output characteristics			
LED Pulse rate	р	ulse/kW	h 1000
LED Pulse duration		ms	30
Static output pulse rate	р	ulse/kW	h 10
Static output pulse duration		ms	100
Static output external voltage		VDC	1030
Static outputs Maximum current		mΑ	50
Insulations			
Rated insulation voltage Ui IEC/EN		V	250
Rated impulse withstand voltage Uimp		kV	6
Operating frequency withstand voltage		kV	4
Mechanical features			
Housing type			Polyamide
Terminals type			Fixed
Conductor cross section			
	min	mm²	1.5



	Max	mm²	10
	min	AWG	16
	Max	AWG	6
Tightening torque (Max)			
		Nm	1.5
		lbin	14
Fixing			Din rail
Weight		g	86
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+55
Storage temperature			
	min	°C	-25
	max	°C	+70
Relative humidity		%	<80
Maximum Pollution degree			2
Mechanical environment			Class M1
Magnetic environment			Class E2
Dimensions			



## Wiring diagrams



## Certifications and compliance

Compliance

CSA 22.2 n°61010-1

EN 50470-1

IEC/EN 61010-1



**ENERGY AND AUTOMATION** 

## **DMED100T1**

## COMPTEURS D'ÉNERGIE 220-240VAC 40A DIRECTE 1U, 1 AUX IMPULSIONS

	UL61010-1	
Certificates		
	cULus	
	EAC	
	RCM	
ETIM classification		
ETIM 8.0		EC001506 - Kilowatt-hour meter