



SICHERUNG FÜR PHOTOVOLTAIK-ANWENDUNGEN, SICHERUNG 10X38MM, AUSSCHALTVERMÖGEN 10KA (1500VDC), 10A

| | 0 | Mary Mary State of the State of |
|--------------------------------|-----|--|
| Product designation | | Fuse 10x85mm |
| Product type designation | | FE |
| Operating voltage type | | DC |
| Electrical features | | |
| IEC maximum rated current (In) | Α | 10 |
| IEC maximum rated voltage (Un) | V | 1500 |
| Rated current (In) | Α | 10 |
| IEC fuse class | | gPV |
| Power consumption at 0,7 In | W | 1.4 |
| Power consumption at In | W | 3.5 |
| Preacring I2t | A2s | 45 |
| Total I2t at 1000Vdc | A2s | 75 |
| Ambient conditions | | |
| Operating temperature | | |
| min | °C | -20 |
| max | °C | +70 |
| Storage temperature | | |
| min | °C | -40 |
| max | °C | +80 |
| Max altitude | m | 3000 |
| Mechanical features | | |
| Weight | g | 19 |
| Dimensions | | |





Certifications and compliance

Compliance

IEC/EN/BS 60269-6

ETIM classification

ETIM 8.0

EC002704 -Cylindrical fuse