



Residual current  
circuit breakers  
(RCCB) with  
overcurrent  
protection  
P1RE  
1P+N  
2  
IEC

Product designation

Product type designation

Number of poles

Number of DIN modules

Compliance

### Electrical features

Rated insulation voltage Ui IEC/EN	V	400
Rated impulse withstand voltage Uimp	kV	4
Rated operational voltage AC (IEC)	VAC	230
Rated frequency	Hz	50/60
Rated current (In)	A	25
Tripping curve		C
Residual operation characteristic		AC
Rated residual current	mA	30
Short circuit rating (IEC)	kA	10
Electrical life	cycles	10000

### Ambient conditions


Operating temperature	min	°C	-25
	max	°C	+60
Storage temperature	min	°C	-40
	max	°C	+80
Max altitude		m	2000

### Mechanical features

Operating position		normal		Vertical plan
Fixing		35mm DIN rail		
Tightening torque for terminals		max	Nm	2
		max	Ibin	15
Terminals tool		Pz 2		
Conductor section				
IEC		min	mm <sup>2</sup>	1
		max	mm <sup>2</sup>	16
AWG/Kcmil		min		16
		max		3
Mechanical life		cycles		20000
Weight		g		205

Frontal IP degree	IP20
Pollution degree	2

## Dimensions



## Certifications and compliance

Compliance	IEC/EN/BS 61009-1
Certifications	EAC TÜV-SUD

## ETIM classification

ETIM 8.0	EC000905 - Earth leakage circuit breaker
----------	--