



ENERGY AND AUTOMATION

electric COMPOSED OF ONE DMG100 MULTIMETER AND N° 3 CTS 150/5A FOR Ø23MM/0.91" CABLE



Product designation			Current transformer kit
Product type designation			DMG100 and 3 CTs 150/5A
Туре			Three-phase + neutral
DIN rail module number			4
Auxiliary supply Us			
Auxiliary rated supply voltage AC		VAC	100240
Auxiliary rated supply voltage DC		VDC	110250
Auxiliary operating voltage range			
AC			
	min	VAC	85
	Max	VAC	264
DC			_
	min	VDC	93.5
	Max	VDC	300
Operational frequency			
	min	Hz	50
	max	Hz	60
Power consumption			
	Max	VA	3.5
Power dissipation Max		W	1.2
Measuring voltage inputs			112
Rated voltage (Ue)			
Tatou voltago (eo)	phase-phase	VAC	690
	phase-neutral	VAC	400
Operating voltage range	pridoc ricultar	77.0	-100
Operating voltage range	phase-phase	VAC	20830
	phase-neutral	VAC	10480
Voltage inputs operational frequency	priase-rieutrai	VAC	10400
voltage inputs operational frequency			45
	min	Hz	45
William San to accompany to a large	max	Hz	66 T DMG
Voltage inputs measurement method			True RMS
			Single. two.
Connection method			three-phase with or without neutral.
Connection method			balanced three-
			phase systems
Current inputs			priase systems
Rated current (le)		Α	5
Measurement range			0.016
Measurement method			
WEASUREMENT METHOD			TDMC
Wododiomon motilod			TRMS
			+20% le through
Overload capacity			





electric COMPOSED OF ONE DMG100 MULTIMETER AND N° 3 CTS 150/5A FOR Ø23MM/0.91" CABLE

ENERGY AND AUTOMATION

Overload peak		A	50A for 1s
Primary current Ipn (/5)		A	150
Secondary output current		A	5
Overload withstand Ipn		%	120
Accuracy		70	120
	VLN voltage		±0.5%
	VLL voltage		±0.5%
	Current		±0.5%
	Frequency		±0.05%
	Active power		±1%
Insulations	The state of the s		
Rated insulation voltage Ui IEC/EN		V	720
Rated impulse withstand voltage Uimp		kV	9.5
Operating frequency withstand voltage		kV	5.2
IEC rated short-time thermal current Ith		Ith for s	4060
IEC rated dynamic current Idyn		Ith for s	2.5
Insulation dry type		11111013	Class E
Mechanical features			Class L
Housing type			Polyamide
Terminals type			Fixed
Conductor cross section			Tixeu
Conductor cross section	min	mm²	0.2
	min	mm²	
	Max	mm²	4
	min	AWG	24
T'. Literature (Mar.)	Max	AWG	12
Tightening torque (Max)		Niss	0.0
		Nm	0.8
		lbin	7
Fixing			Din rail
Weight		g	856
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-20
	max	°C	+60
Storage temperature			
	min	°C	-30
	max	°C	+80
Relative humidity		%	<90
Maximum Pollution degree			2
Protection degree			IP30
ETIM classification			
			EC002301 -
ETIM 8.0			Multifunction
			measuring
			instrument