



Product designation				Switch disconnecter
Product type designation				GA
Number of poles				Nr. 3
Operating voltage type				AC
Contact characteristics				
IEC Conventional free air thermal current I <sub>th</sub>				A 32
Rated insulation voltage U <sub>i</sub> IEC/EN				V 1000
Rated impulse withstand voltage U <sub>imp</sub>				kV 8
Operating current I <sub>e</sub>				
AC21A				
400V				A 32
500V				A 32
690V				A 32
AC22A				
400V				A 32
500V				A 32
690V				A 32
AC23A				
400V				A 32
500V				A 25
690V				A 25
Power dissipation per pole max				W 0.6
Rated operational power AC23A				
400V				kW 15
690V				kW 22
Rated short time current (1s) I <sub>cs</sub> (rms)				kA 0.8
Conditional short-circuit current (rms)				kA 10
Short-circuit protection with fuse				Class/A gG32
Making capacity AC23A 400V				A 400
Breaking capacity AC23A 400V				A 320
Mechanical life				cycles 100000
Electrical life AC21A				cycles 100000
Mechanical features				
Operating position				
normal allowable				Vertical plan Any
Fixing				Screw / DIN rail 35mm
Terminals				
type				Pillar
width mm				5.6
height mm				6.5
screw				M4
tool				Phillips 2

Tightening torque for terminals

min	Nm	1.8
max	Nm	2
min	lbin	16
max	lbin	18

Conductor section

IEC min	mm <sup>2</sup>	0.75
IEC max	mm <sup>2</sup>	16
AWG/kcmil min		18
AWG/kcmil max		6

Ambient conditions

Operating temperature

min	°C	-25
max	°C	55

Storage temperature

min	°C	-40
max	°C	70

Max altitude

m	3000
---	------

Resistance & Protection


Frontal IP degree

IP20


Pollution degree

3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n°60947-4-1

IEC/EN 60947-1

IEC/EN 60947-3

UL60947-4-1

Certifications

CCC

CSA C22.2 n°60947-4-1

cULus according to UL60947-4-1

EAC

KEMA

ETIM classification

ETIM 8.0

EC000216 -  
Switch  
disconnector