



## Product designation

## Product type designation

Selector switch  
actuators lever -  
3 position  
LPCS13

## General characteristics

|                          |                      |
|--------------------------|----------------------|
| Colour                   | Black                |
| Type of positions        | Selector switch      |
| Material                 | Polyamide            |
| IEC degree of protection | IP66, IP67 and IP69K |

## Mechanical features

|                  |        |          |
|------------------|--------|----------|
| Mechanical life  | cycles | 1000000  |
| Mounting adapter |        | LPXAU120 |
| Weight           | g      | 37       |

## UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

## Ambient conditions

### Temperature


#### Operating temperature

|     |    |     |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +70 |

#### Storage temperature

|     |    |     |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +85 |

## Dimensions



## Certifications and compliance

### Compliance

CSA C22.2 n° 14  
IEC/EN/BS 60947-1  
IEC/EN/BS 60947-5-1  
UL508

### Certificates

CCC  
cULus

## ETIM classification

ETIM 8.0

EC000222 -  
Front element for  
selector switch