



°C

°C

-40


+85

min

max

Product designation Product type designat	ion			Selector switch actuators lever - 2 position LPCS12
General characteristic				
Colour				Black
Type of positions				Selector switch
Material				Polyamide
IEC degree of protect	tion			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Mounting adapter				LPXAU120
Weight			g	37
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
		max	°C	+70
	Storage temperature			

Dimensions



Certifications and compliance

Complian	ce	
	CSA C22.2 n° 14	
	IEC/EN/BS 60947-1	
	IEC/EN/BS 60947-5-1	
	UL508	
Certificate	95	
	CCC	
	cULus	
ETIM clas	sification	
LPCS120	The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding	1 / 2

LPCS120

SELECTOR SWITCH ACTUATOR KNOB Ø22MM PLATINUM SERIES CHROMED PLASTIC, 2 POSITION, 0 - 1



EC000222 -Front element for selector switch

ETIM 8.0